

 **Superior**

**LL
SERIES**

'Superior Slashers' Medium Heavy Duty



LL6 with Flexible Tower &
Opt. 400 x 8 Puncture
Proof Castor Wheel.



Height Adjust. 100 x 8 Castor Wheel, Laminated
Cutting Head with 16mm Step Down Blades,
Heat-Treated Bustrus and Hi-Tensile Bolts.

Major Features...

- Strength & Durability
- 5mm Fabricated Body
- 75hp G/box, Clutch & D'shaft
- Bottom Seal Protection
- Hi Speed Cutting Head
- 250mm Sides for Volume

**LL
SERIES**

Superior...the grass control specialists

'Superior Slashers' Medium Heavy Duty

LL SERIES

Major Technical Features	LL4	LL4.5	LL5	LL6	LL7
Cutting Width – Imperial (Metric)	4' (1.2m)	4'6" (1.35m)	5' (1.5m)	6' (1.8m)	7' (2.1m)
Overall Width	4'4" (1.25m)	4'10" (1.45m)	5'4" (1.60m)	6'4" (1.90m)	7'4" (2.20m)
Weight (kg)	250	280	350	450	650
Recommended Tractor Min. Horsepower (kw)	16 (9)	25 (12)	30 (19)	35 (22.5)	40 (30)
Gearbox Horsepower Rating	75	75	75	75	120
Fully Fabricated All Steel 5mm Body	✓	✓	✓	✓	✓
Single Rotor with Two Swing-Back Blades	✓	✓	✓	✓	✓
Cat 1 & 11 with Flexible Tower	Rigid	✓	✓	✓	✓
4 Plate Integrated Clutch & D'Shaft	✓	✓	✓	✓	÷
Adjustable Skids with 250mm Sides	✓	✓	✓	✓	††
Blade Tip Speed 'fpm @ 540 pto (Std. Ratio)	13101	14740	16377	14867	17344
Blade Tip Speed 'fpm @ 540 pto (High Ratio)	13101	14740	16377	19653	N/A
Blade Tip Speed 'fpm @ 750 pto*	18197	15486	17207	20648	16500
Blade Tip Speed 'fpm @ 1000 pto*	18354	20648	15714	18857	22000

† separate clutch and driveshaft

†† Opt. Skids to LL7

*gearbox ratio to match intended pto

Optional Extras

(items below available to all models P.O.A.)

- Hot Dipped Galvanised Body
- LL Series Castor Wheel Solid 400 x 8
- LX EHD Castor Beam & Std Wheel's
- Single Leg Fork with 400 x 8 Wheel
- 520 x 10 Monofill Wheel's
- 120hp G'box 13" 20 Spline Input Shaft
- Triangle Cutting Head with 3 Blades
- Straight, Suction Lift, and Turf Blades
- Full Steel Backflap or Full Rubber
- Safety Chains Front &/or Rear
- Safety Support Stands
- Extra Gusseting & Stone Protection
- Anti-Window Plate
- Adjustable Skids to LL7
- Mulch Plates
- Offset Tower
- Side Discharge Chute
- Full Rear Height Adjustable Roller
- Full Height Adjust. Rollers Front & Rear
- Hydraulic Height Control to Rear Wheel
- Trail Versions with Draw Bar,
- Hyd. Height Control



Galv. LL6 with Twin LX Castor Wheels (400 x 8).



Galv. LL6, 120hp G'box, Single LX EHD Castor Wheel & Safety Chains Front & Rear.

Superior
Equipment Australia Pty. Ltd. Adv 50 054 422 162

5 Quindus Street Wacol 4076
Brisbane Queensland Australia

Phone: (07) 3271 3177 Int.: 61 7 3271 3177
Fax: (07) 3271 3285 Int.: 61 7 3271 3285

Email: superiorequipment@uq.net.au
Website: www.superiorequipment.com.au



CONTACT YOUR LOCAL SUPERIOR DEALER:

Superior...the grass control specialists