



Front and rear mowers for professional use

• Green maintenance • Agriculture • Tractors from 65 up to 105 HP



ProTeam

FERRI



Versatile
MKD

Front and rear mowers for professional use

• Green maintenance • Agriculture • Tractors from 65 up to 105 HP

ProTeam
FERRI



The new MKD shredder is planned for a professional use for green maintenance. Suitable for both front and rear applications by means of its standard double drive multiplier and for its removable three-point linkage. Can be used with a 540 rev or 1,000 rev, by reversing the pulley position.

Technical specifications

Mod.		MKD 200	MKD 230	MKD 250	MKD 280
Cutting width	cm	200	223	250	274
Weight	Kg	775	838	918	985
Tractor HP Required power	HP	65/75	75/85	85/95	95/105
Hydraulic side shift	cm	60	60	70	70
Belts	n°	3	3	4	4
	Rotor speed with 540 rpm Pd.F.	n° 2215	2215	1970	1970
	Rotor speed with 1000 rpm Pd.F.	n° 2342	2342	1990	1990

Working positions



Flange



Tubular skids



Double shaft gearbox



Adjustable belt-tensioner




Side flanges bolted to rear roller



Hydraulic side shift

Double skin


Working position



MKD 200




MKD 230



MKD 250



MKD 280



Blades

	MOD.	MKD 200	MKD 230	MKD 250	MKD 280
Multi-use - straight blades Ø max cm 5	n°	72 (48+24)	84 (56+28)	90 (60+30)	108 (72+36)
Articulated "V" - straight blades Ø max cm 3	n°	136 (92+46)	156 (104+52)	-	-
Hammer blades Ø max cm 6	n°	24	28	30	36

FERRI



FERRI srl

Via C. Govoni, 30 - 44030 Tamara (FE) Italy
 Tel. +39-0532.866886 Fax +39-0532.866851
 www.ferrisrl.it - info@ferrisrl.it

FERRI France s.a.r.l.

75 RN 20 - 31790 SAINT-JORY
 Tél. 05 61 35 52 05 - Fax 05 61 35 74 18
 e-mail: ferrifrance@caris-aa.com